

MiPlank

Luxury Vinyl Flooring

The MiPlank of loose lay vinyl tiles and planks offer authentic reproductions of beautiful natural materials presented in an adhesive free product designed to reduce installation time. As Expona Simplay can be installed over many different types of existing floorcoverings, subfloor preparation is significantly reduced making it a practical choice for many heavy commercial applications including office and retail sectors, and because it is loose lay each plank or tile can be installed, lifted and reinstalled elsewhere without leaving any residue.



FLOORCARE



- Polyflor MiPlank incorporates a polyurethane reinforcement, which protects the floorcovering by resisting soiling and scuffing. This protection facilitates a reduction in the intensity of the construction clean and provides the foundation for the ongoing maintenance regime. This easier cleanability offers maintenance cost savings when compared with non-treated materials.
- The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your floorcovering.

INITIAL CONSTRUCTION CLEAN



After Installation

- Sweep or suction clean to remove dust and grit
- Damp mop with a neutral cleanser. When damp mopping, ensure the minimum solution is used.
- The minimum amount of liquid should be used to prevent it penetrating into the seams and joints.

ROUTINE MAINTENANCE



Daily

- Mop sweep or vacuum to remove dust and loose dirt.
- As required, spot clean with a neutral cleanser to remove stubborn marks.

Weekly/Monthly

- As required, clean the floor using a neutral cleanser and microfibre mop.
- The minimum amount of liquid should be used to prevent it penetrating into the seams and joints.

APPLICATION OF A FLOOR DRESSING - FOR HEAVY USE AREAS



- Should you wish to apply a floor dressing to the floorcovering to provide extra protection in heavily trafficked areas, please follow the details of the procedure below. Using an applicator and tray, or Kentucky mop with wringer and bucket, the first coat should be applied thinly and evenly across the floor, to within 200mm of the skirtings. It should then be left to dry. This normally takes approximately thirty minutes, depending on the ambient conditions and the thickness of the coating.
- Using an applicator and tray, or Kentucky mop with wringer and bucket, the first coat should be applied thinly and evenly across the floor, to within 200mm of the perimeter. Use the minimum amount of liquid and leave it to dry. This normally takes approximately thirty minutes, depending on the ambient conditions.
- When the first coat is dry, a second coat should be applied at right angles to the direction of the first coat. Subsequent coats should then be applied at right angles, and the final coat should be applied up to 20mm of the perimeter.
- Two to three thin coats are usually sufficient to provide excellent resistance to abrasion, scuffing and removal of black heel marking. However, be guided by your own periodic assessments for the particular location.
- In order to minimise costs, subsequent polish applications may be applied only to traffic paths.
- Periodically - generally every six months - assess the appearance of the floor. If there is an unacceptable build-up of polish, this should then be stripped using a dry or low liquid method. The polish can then be reapplied as per the instructions above.

NOTE: This maintenance regime requires the installation of an effective barrier matting system.



- Cleaners and detergents should be diluted as per the manufacturer's instructions.
- For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
- Always follow the Health and Safety guidance provided.
- At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.

REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.



APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

PRODUCT	NEUTRAL CLEANSER	ALKALINE CLEANSER	MAINTAINER/ WASH & WAX	FLOOR POLISH	POLISH STRIPPER	POWER CLEANER (Spot Cleaner)
DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	Active Cleaner	Clean and Strip	Floor Cleaner R1000	Floor Shine Floor Mat Secura Hard Sealer	Clean & Strip	Turbo Strip
BRITISH NOVA Tel: 01295 251721 www.cleenol.co.uk	Liquid 99	Novaways Nova Multi Purpose Sanitiser Nova Safety Floor Cleaner	Novacare	Nova Long Life Gloss Nova Long Life Satin	Nova Starbrite	Nova Multi Purpose Sanitiser
PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	Natural Multi Surface Floor Cleaner	Alkleen Ultrapac Renovate Powerclean	Protreat	Proshine	Prostrip	Powerclean
EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	High Class	E.M.C Plus Versatile Lift	Clean & Shine	Sustain Mexapol Enhance	Easystrip Sure Strip	Lift
ECOLAB LTD Tel: 01793511221 www.ecolab.com	Maxx Brial 2 Neomax Star Plus	Regain Neomax GMS Maxx Magic 2	Indur XL Fresh Indur Brilliant Plus Maxx Indur 2	Isi Star Maxx Isi 2 Tuklar Maxx	Maxx Bendurol 2 Maxx Forte2l	Pep Active
DIVERSEY UK LTD Tel: 01604405311 www.diversey.com	Taski Jontec 300 Carefree Stride 1000	Carefree Stride 2000 Taski Jontec Forward	Carefree Stride 3000 Taski Jontec Tensol	Carefree Eternum Taski Jontec Eternum	Carefree Stripper Carefree Speed Stripper	Taski Sprint Spitfire
SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk	Frequent Use Scrubber Drier Detergent Sabre	Multi-Purpose Cleaner Selclen S Triple	Selsheen Fast Lane Low Foam Floor Maintainer	Seldur Selexel Diamond Brite	Selstrip Selspeed Selate	Maxima
PREMIERE PRODUCTS Tel: 01298 28505 www.premiereproducts.co.uk	Low Foam	MP9 MP10	Clean & Buff GC10	Platinum 25 Premac Super	Premstrip	Force

CHEMICAL FREE CLEANING	HOMOGENEOUS		POLYSAFE APEX POLYSAFE ULTIMA
	HETEROGENEOUS LUXURY VINYL TILES	SAFETY	
DECITEX Tel: www.	Decitex Disposable Machine washable (various)	Decitex Ultimate Dx1 Dx1 Ultimate Duo-White M800	Decitex Ultimate Duo- White

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at www.polyflor.com

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.