

# Acoustix Forest fx PUR

## PRODUCT SPECIFICATION

### Key Features

- > A collection of wood designs in vinyl sheet format
- > 19dB acoustic performance
- > Low cost, polish-free maintenance
- > High traffic commercial interiors



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.7mm
Wear Layer	ISO 24340 (EN 429)	0.65mm
Total Weight	ISO 23997 (EN 430)	2550g/m <sup>2</sup>
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	8	-	40m <sup>2</sup>

Performance Requirements	Standard	Result
General Performance	ISO 11638 (EN 651) ASTM F1303	Conforms Type I, Class I, Class C Backing
Use Area	ISO 10874 (EN 685)	23, 34, 42
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 651	Group T
Reaction to Fire	EN 13501-1 ASTM E648 AS ISO 9239.1	Class Bfl-S1 Class 1 ≥ 8kW/m <sup>2</sup>
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F1914 ASTM F970 (Modified) ISO 24343-1	≤0.005" ≤0.009" (750psi) ≤0.20mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
Flexibility	ISO 24344 (EN 435) ASTM F137	(Method A) Pass 20mm ø 0.25" Pass
Thermal Resistance	ISO 12667	0.0525m <sup>2</sup> K/W
Underfloor Heating		Suitable, max 27°C

Light Fastness	ISO 105-B02 (Method 3)	≥6
Furniture Leg	ISO 16581 (EN 424)	Pass
Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$ - Meets
Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$ - Meets

## Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 415
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

## Acoustic Performance

	Standard	Result
Impact Sound Reduction	ISO 10140-3	19dB
Sound Transmission Coefficient	ASTM E90/492	STC 56
Impact Insulation Class	ASTM E90/492	IIC 57

## Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



BS EN 14041



EN 14041

## Polyflor Head Office

101 Prosperity Way, Dandenong South, VIC, 3175 • Tel: 1800 777 425 • Email: sales@polyflor.com.au • [www.polyflor.com.au](http://www.polyflor.com.au)

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

# Acoustix Forest fx PUR



## RANGE SHADES



**Warm Beech 3295**  
plank size in sheet: 100 x 500mm  
w/r 3290 LRV 34



**American Oak 3385**  
plank size in sheet: 100 x 1000mm  
w/r 3380 LRV 33



**Rustic Oak 3335**  
plank size in sheet: 84 x 332/664mm  
w/r 3330 LRV 25



**European Oak 3345**  
plank size in sheet: 100 x 1000mm  
w/r 3340 LRV 20



**Oiled Oak 3095**  
plank size in sheet: 167 x 1500mm  
w/r 2990 LRV 35



**Classic Oak 3125**  
plank size in sheet: 167 x 1500mm  
w/r 3330 LRV 30



**Smoked Oak 3155**  
plank size in sheet: 167 x 1500mm  
w/r 3150 LRV 14



**Classic Walnut 3235**  
plank size in sheet: 167 x 1000mm  
w/r 3230 LRV 13

w/r - Weld Rod

LRV - Light Reflectance Value

### Polyflor Head Office

101 Prosperity Way, Dandenong South, VIC, 3175 • Tel: 1800 777 425 • Email: sales@polyflor.com.au • [www.polyflor.com.au](http://www.polyflor.com.au)

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

VI